

## DGO series - Large - Rubber hose



### Technical characteristics

**Technology:** Pipe locked with ratchet stop

**Max operating pressure:** 12 bar

**Construction:** Epoxy-coated steel case

**Connection:** 1 m of inlet supply hose

**Equipped with:** Fixed bracket


Fixed bracket

Inlet: G 3/8 F

Inlet: G 1/2 M for DGO 1320 + DGO 1610  
+ 1 m hose

Pressure: 12 bar

Temperature: -15°C to +65°C

	A (mm)	B (mm)	C (mm)	ID/OD (mm)	Length (m)	Coupler	Flow rate (l/min)	Swivel inlet (BSPP)	Weight (kg)	Parts Numbers
	485	475	237	10 x 17	25	ESI 07	500	G 3/8 F	26	<b>DGO 1025ES</b>
	485	475	237	13 x 20	20	ESI 07	1000	G 1/2 M	27	<b>DGO 1320ES</b>
	485	475	237	16 x 23	10	ESI 11	3000	G 1/2 M	27	<b>DGO 1610ES</b>
	485	475	237	10 x 17	25	ISI 06	500	G 3/8 F	26	<b>DGO 1025IS</b>
	485	475	237	13 x 20	20	ISI 08	1000	G 1/2 M	27	<b>DGO 1320IS</b>
	485	475	237	16 x 23	10	ISI 11	3000	G 1/2 M	25	<b>DGO 1610IS</b>
	485	475	237	10 x 17	25	CSI 06	500	G 3/8 F	26	<b>DGO 1025CS</b>
	485	475	237	13 x 20	20	CSI 08	1000	G 1/2 M	27	<b>DGO 1320CS</b>
	485	475	237	16 x 23	10	ISG 11	3000	G 1/2 M	25	<b>DGO 1610</b>