

## DMO - DGO GR series (Lubricants) - Rubber hose - High pressure - Grease




### Technical characteristics

**Technology:** Pipe locked with ratchet stop

**Construction:** Epoxy-coated steel case

**Equipped with:** Fixed bracket

Fixed bracket  
Inlet: G 1/4 F  
Max Pressure: 400 bar  
Temperature: -10°C to +100°C

|  | A<br>(mm) | B<br>(mm) | C<br>(mm) | ID/OD<br>(mm) | Length<br>(m) | Outlet BSPP<br>male thread | Swivel inlet<br>BSPP male<br>thread | Weight<br>(kg) | Parts Numbers     |
|--|-----------|-----------|-----------|---------------|---------------|----------------------------|-------------------------------------|----------------|-------------------|
|  | 485       | 475       | 237       | 6.4 x 14.7    | 10            | G 1/4                      | G 1/4                               | 18.5           | <b>DMO 0610GR</b> |
|  | 485       | 475       | 237       | 6.4 x 14.7    | 15            | G 1/4                      | G 1/4                               | 20.5           | <b>DMO 0615GR</b> |
|  | 485       | 475       | 237       | 6.4 x 14.7    | 20            | G 1/4                      | G 1/4                               | 27             | <b>DGO 0620GR</b> |