


LEGEND

HPG	High pressure gauge
LPG	Low pressure gauge
MW	Water pressure gauge
RM	Manual water filling cap
VSC	Water drain valve
SFAF	Free cooling manual air vent
VSCF	Free cooling water drain valve
ATS	Spring type antivibrant mounting (Opt)
ATV	Rubber type antivibrant mounting (Opt)


LIFTING AND CARRIAGE PRECAUTIONS

- Check the weight on the CE label to select appropriate lift equipment .
- Before lifting the unit make sure that the external panel is firmly fixed in place.
- To use only lifting points provided.
- The chains or slings must be of equal length.
- To use a spread-bar to avoid damage to the unit.
- The movement must be performed with caution and avoid abrupt movements.
- Never move the unit on rollers.
- Never lift the unit using a fork-lift.



ATTENTION:

THE FOLLOWING DIMENSIONS AND WEIGHTS
DO NOT INCLUDE THE PACKAGING

Scala-Scale	Data-Date 23/01/14	Dis.to-Drawn B.C.	N°Pezzi		
Peso-Weight Kg.	Materiali-Materials				
Denominazione-Denomination WATER CHILLERS mod. ENRF.100/CS.T.WP				DIS.-DRAW N.	DIM-ENRF-100ST0100
Particolare-Detail Overall dimension - Lift Instruction				Rev.	04 - B.C. - 10/12/20
REFRIGERANT R410A / R32 /R454B				PROGRAM.N.	

SAFETY PIN
(SAFETY DEVICE)

PIPE Ø48 Thk. 5mm min.

DISC OF CLOSING

DETAIL B