

Air random orbital sander 3" - In case



Technical characteristics

Max operating pressure: 6,2 bar


Applications: Stripping and preparation prior to painting

Highlight: Easy to use and low sound level

Connection: Supplied with 3 adaptors: ISO 6150 B; European 7,4 mm; ARO 210

Supplied in case with:

- 1-piece 3" Velcro backing pad
- 1-piece 2" Velcro backing pad
- 10-piece 3" abrasive disc 600 grit
- 10-piece 3" abrasive disc 400 grit
- 10-piece 3" abrasive disc 320 grit
- 10-piece 2" abrasive disc 600 grit
- 10-piece 2" abrasive disc 400 grit
- 10-piece 2" abrasive disc 320 grit

| | A (mm) | B (mm) | Offset (mm) | Diameter (plate) | Consumpt (l/min) | Power | Rotation speed (rpm) | BSPT female thread | Sound level (dB(A)) | Weight (kg) | Parts Numbers |
|--|-----------|-----------|----------------|---------------------|---------------------|--------------------|----------------------------|--------------------------|---------------------------|----------------|--------------------|
|  | 165 | 158 | 3 | 75 mm 3" | 113 | 0.45 CV - 330 W | 16 000 | R 1/4 | 80 | 2.0 | TPS E16000K |